

SENKO

*For a perfect
warm home!*



**PRODUCT
CATALOG**

2014/2015

www.senko.hr



ADVANTAGES OF SENKO COOKERS



- An external combustion air supply is mounted at the rear side of the cooker.
- All SENKO cookers are coated with firebrick, to maximally use all generated heat, which results in lower fuel consumption for equal heating of the room.
- Construction solutions and intake of secondary air into the firebox provide an additional fuel efficiency and combustion of harmful gases - SENKO GREEN LABEL
- To change the grate's summer – winter position during firing, some models offer thread driven firebox grate.
- All models are equipped with glass firedoor to enable control of fuel combustion.
- Chimney / Flue connection is height adjustable to facilitate easier installation of the cooker.
- Cooking plates are 8 mm thick and ensure long operational life of the cooker.



CE is a mark of the manufacturer that the product meets all requirements for safety and health in terms of EU directives and harmonized standards.



Quality management system: the success of leadership of the organization and its operation requires managing in a systematic and transparent manner.



SYMBOLS

- | | | |
|------------------------------------|----------------------------------|---|
| Nominal heat output | Amount of water in boiler | Firebox ↑ Summer ↓ Winter |
| Dimensions (w × d × h) | Primary air inlet | Firebox door |
| Cooking plate (w × d) | Flue gases exhaust | Oven |
| Oven dimensions (w × d × h) | Required flue draught | Front look |
| Weight | Air regulation | Certified according to the following EN standard |
| | Boiler protection | |

L = chimney connection on the left side
D = chimney connection on the right side

SOLID FUEL COOKERS

FOR CENTRAL HEATING



E 2320 L/D C-20

INOX LUX - without oven

- 25
- 60x64x85cm
- 47x45cm
- 160kg
- 20L
- Ø130
- Ø100

- 12 Pa
- Primary: auto
Secondary: manual
- Prepared for boiler overheating thermal protection
- Casted grate - movable (mechanism)
- Fireproof glass
- INOX PC-3 PC-5 PC-6 PC-7
- EN 12815



E 2330 L/D C-30

INOX LUX - without oven

- 35
- 60x78x85cm
- 47x59cm
- 180kg
- 28L
- Ø130
- Ø100

- 16 Pa
- Primary: auto
Secondary: manual
- Prepared for boiler overheating thermal protection
- Casted grate - movable (manual)
- Fireproof glass
- INOX PC-3 PC-5 PC-6 PC-7
- EN 12815



SENKO



E 2280 L/D C-25

INOX LUX

25 kW _N	35
100x64x85cm	100x78x85cm
86x45cm	86x57cm
36x46x26cm	36x60x26cm
235kg	270kg
20L	28L
Ø130	Ø150
Ø100	Ø100
12 Pa	16 Pa





Primary: auto
Secondary: manual

Prepared for boiler overheating thermal protection

Casted grate - movable (mechanism)

Stainless steel interior, glass door with thermometer

Fireproof glass

-  INOX
-  PC-3
-  PC-5
-  PC-6
-  PC-7
-  EN 12815

E 2235 L/D C-35

INOX LUX

Suitable for central heating




Combination with existing heating system

Primary: auto
Secondary: manual

Prepared for boiler overheating thermal protection

Casted grate - movable (manual)

Stainless steel interior, glass door with thermometer

Fireproof glass

-  INOX
-  PC-3
-  PC-5
-  PC-6
-  PC-7
-  EN 12815

Suitable for central heating



Combination with existing heating system

Suitable for central heating



Combination with existing heating system

SOLID FUEL COOKERS

FOR CENTRAL HEATING



E 2370 L/D C-30-P

INOX LUX

kW_N 30

Ø130

110x64x85cm

Ø100

45x44x28cm

14 Pa

260kg

Primary: auto
Secondary: manual

22L

Stainless steel interior, glass door with thermometer

97,5x43cm

Prepared for boiler overheating thermal protection

Casted grate - movable (mechanism)

Fireproof glass



INOX PC-3 PC-5 PC-6 PC-7

EN 12815



Suitable for central heating



Combination with existing heating system

FIREBOX POSITION



Summer regime



Winter regime



Exclusive line duo



EXTRA RUSTIK **E 2125 L/D C-20 2P**
 GLASS **E 2220 L/D C-20 2P**
 GLASS DESIGN **E 2420 L/D C-20 2P**

E 2135 L/D C-30 2P EXTRA RUSTIK
E 2230 L/D C-30 2P GLASS
E 2430 L/D C-30 2P GLASS DESIGN



140x68x85/126cm

33x44x22cm

Ø150

Ø100

Primary: auto
 Secondary: auto

Prepared for boiler overheating
 thermal protection

EN 12815

25 35



140x82x85/126cm



33x55x22cm



Ø150



Ø100



Primary: auto
 Secondary: auto



Prepared for boiler overheating
 thermal protection



EN 12815



Combination
 with existing
 heating system

Combination
 with existing
 heating system

Do you want to arrange your home in a rustically looking area with charm and perfect warmth? Then we can only recommend you to choose our exclusive cooker with the look of an old kitchen cooker, like such from old households with big ovens and cooking areas. We took the knowledge of old class kitchen cooker masters and combined it with the newest technology.

The result is our newest model, a cooker that looks rustically but is very economic and efficient. Exterior plates can consist of ceramic tiles or tempered glass in different colours. You can choose your own look, so the cooker can be in accordance with your interior design. Every model in this series can be adjusted; you just need to name your wishes.

SOLID FUEL COOKERS



E 2375 L/D SG-75 INOX



kW_N 7,5

75x65x85/92cm

66x49cm

33x44x27cm

135kg

Ø120

Ø100

12 Pa

EN 12815

Primary: manual;
Secondary: auto

Stainless steel interior,
glass door with thermometer

Fireproof glass

INOX PC-3 PC-5 PC-6 PC-7

E 2390 L/D SG-90 INOX

kW_N 7,5

90x65x85/92cm

82x49cm

40x44x23cm

170kg

Ø120

Ø100

12 Pa

EN 12815

Primary: manual;
Secondary: auto

Stainless steel interior,
glass door with thermometer

Fireproof glass



INOX PC-3 PC-5 PC-6 PC-7

CENTRAL HEATING FIREPLACES



E 2285 FIREPLACE CENTRAL

kW_N 30-35kW

↕ 85x87x125cm

⚖ 240kg

📄 55L

🔄 Ø200

🔄 Ø150

🔌 Automatic

📄 Prepared for boiler overheating thermal protection

🔥 Fireproof glass

✓ EN 13229

Suitable for central heating

Combination with existing heating system

E 2284 FIREPLACE CENTRAL

kW_N 20-25kW

↕ 65x75x115cm

⚖ 155kg

📄 32L

🔄 Ø200

🔄 Ø100

🔌 Automatic

📄 Prepared for boiler overheating thermal protection

🔥 Fireproof glass

✓ EN 13229

Suitable for central heating

Combination with existing heating system



www.senko.hr

SENKO



LOFSB



SENKO GREEN LABEL

28 YEARS OF EXPERIENCE AND DEVELOPMENT

We reserve the right to change technical details and colours of products, mentioned in this catalog, without prior notice.